



DC Inverter
Cooling only

Airwell

WFAE Window

A

Unique
solution



WFAE RC
included

+ PRODUCT

- WFAE RC remote control included
- Monobloc solution
- No fluid handling

FEATURES

TECHNOLOGY



NIGHT MODE



AUTO RESTART
(MEMORY)

INSTALLER FUNCTIONS



SELF DIAGNOSTIC

THE «SUSTAINABLE DEVELOPMENT»

> Environmentally friendly R32 refrigerant, low energy consumption.

THE «USER»

> Ideal for modular constructions.

THE «INSTALLER»

> Ease of installation.

THE «TECHNOLOGY»

> Inverter technology.

TECHNICAL DATA

INDOOR UNIT		WFAE-025C-09M25	WFAE-035C-09M25
Part number		7MB050001	7MB050002
Phase		Single phase	Single phase
COOLING			
Rated power	kW	2.75	3.70
Pdesignc	kW	2.75	3.70
Rated power input	kW	0.81	1.09
SEER/Energy label		5.10/A	5.10/A
Operating limits	°C	18°/43° Dry bulb	
INDOOR UNIT			
Sound pressure level at 1 m (LS/MS/HS)	dB(A)	45/47/49	45/47/49
Airflow (LS/MS/HS)	m³/h	310/350/380	400/450/490
Dehumidification	l/h	1.00	1.20
Compressor type		Rotary	Rotary
Outline dimensions (WxHxD)	mm	560x375x710	660x428x700
Package dimensions (WxHxD)	mm	623x425x806	739x515x793
Net weight/Gross weight	kg	34/36.7	46/50
POWER SUPPLY			
Phase/Voltage/Frequency		1P/230V/50Hz	1P/230V/50Hz
Power supply side		Indoor	Indoor
Power cable section	mm²	3x1.0	3x1.5
Fuse rating am (D curve)	A	10	10
PIPE LINE			
Refrigerant/GWP		R32/675	R32/675
Charge	kg	0.51	0.63